

Rodoirs avec liant galvanique, exécution longue  
*Hones with galvanic bond, long execution*  
 Honahlen mit Galvanischebindung, langer Ausführung



Ø	L1	L2	E	T	n	B	A	D	X	L <sub>max</sub>
11.00	150	115	---	42	---	---	25	15 - 150	0.3	69
12.00	150	115	---	42	---	---	25	15 - 150	0.3	69
13.00	150	115	---	42	---	---	25	15 - 150	0.3	69
14.00	150	115	---	42	---	---	25	15 - 150	0.3	69
15.00	160	125	---	42	---	---	30	15 - 150	0.3	74
16.00	160	125	---	42	---	---	30	15 - 150	0.3	74
17.00	160	125	---	42	---	---	30	15 - 150	0.3	74
18.00	165	130	---	42	---	---	30	15 - 150	0.3	79
19.00	165	130	---	42	---	---	30	15 - 150	0.3	79
20.00	165	130	---	42	---	---	30	15 - 150	0.3	79
21.00	175	135	---	42	---	---	30	15 - 150	0.3	84
22.00	175	135	---	42	---	---	30	15 - 150	0.3	84
23.00	175	135	---	42	---	---	30	15 - 150	0.3	84
24.00	175	135	---	42	---	---	30	15 - 150	0.3	84
25.00	175	135	---	42	---	---	30	15 - 150	0.3	84

